



R4-TEMP

External temperature sensor

- + This temperature sensor can be used with any 401, 420, 450 & 490 series clock to provide either an alternating or continuous display of temperature information.
- + The sensor is housed in a two part, clip together, ventilated case. The module may be mounted on a suitable vertical surface, either by the use of two strips of double sided tape or by mechanical fixing via two screws through the marked positions in the detachable base plate of the unit. The module must be mounted in a position where it is not subject to direct rain or other water spray.
- + Two temperature display modes are available. The temperature may be displayed continuously or alternately exchanged with the hours and minutes time display. When the alternate time/temperature display mode is selected the period between display changes may be adjusted from between 1 and 15 seconds.
- + The R4-TEMP module is normally supplied with a three core, 5 m connecting cable which may be user extended up to a maximum of 100 m.

Technical specifications:

UID-Nr.: ATU 45163905 :: ARA-Nr.: 10722

Displayed temperature range:	-17 °C to +50 °C
Temperature calibration:	±5°C
Dimensions (WxHxD):	70 x 70 x 25 mm









MATTIG-SCHAUER GmbH Gorskistraße 19 :: A-1230 Wien
Tel.: +43 (1) 61055-0 :: Fax: +43 (1) 61055-30 :: e-mail: office@mattig-schauer.at :: www.mattig-schauer.at