



**RA474AIL30/405S**

**Digital LED time zone display**

- + Indication of 4 programmable time zones
- + Time display of hours and minutes
- + Pre-programmed seasonal time changes for each zone individually
- + Modes of operation:
  - + Stand-alone quartz clock
  - + Slave clock (synchronised through a series HU master clock)
  - + Synchronisation from DCF- or GPS-receiver directly
- + Red bright LED dot-matrix display with 50 mm digit height
- + Readability up to 20 m
- + Free programmable city names with max. 10 characters per zone
- + Character height of city names 30 mm
- + Configuration via RS232 interface and PC
- + incl. CD-ROM with software for time zones control
- + Display brightness adjustment manually or automatically
- + Infrared remote control unit R408IR in delivery included
- + To be used indoors
- + Software:
  - + Windows application, executable under Windows 98, NT4, 2000 and XP
  - + Configuration of city names, time zones and date of summer-/winter time changes for each zone
  - + Software active only, if display information shall be modified
  - + Programm requires a PC Microsoft Windows 9x, NT4, 2000 or XP with serial RS232 port (not included in delivery)

**Technical specifications:**

Case:	Aluminium, nature anodised
Accuracy:	<1 s/week at 20...25 °C
Power supply:	230 V AC / 50 Hz
Current consumption:	<0.45 A
Ambient temperature:	0...50 °C
Dimensions (WxHxD):	1204 x 180 x 58 mm
Weight:	approx. 7 kg



MATTIG



WENZEL



NEUMANN

**Options:**

R474AIL30/x05S:	Versions with 3 to 8 time zones possible
R474AIL30/405P:	Double sided version with ceiling bracket
R474AIL30/405E:	Version for flush mounting in a panel with rear access
R474AIL30/405B:	Version for flush mounting with steel mounting box for solid wall
R4-DCF:	DCF-77 radio synchronisation antenna
GPS-ANT1HS:	GPS synchronisation antenna



MATTIG



WENZEL



NEUMANN