



GONG-MVB

Electronic gong

- + To be used for signalisation of breaks, fire alarm and similar applications in schools, industrial buildings, sports halls and so on
- + Big selection of melodies and additional alarm function
- + Selectable supply voltage up to 230 V
- + 18 brilliant sounds (2-/3-Chime, Westminster bell sound, pop, special sound for hearing-impaired people, classical music, and so on)
- + Signalling changeable from melody to alarm sound
- + Adjustable sound volume
- + Silence function with checking LED (Muting with one push-button)
- + User-friendly through opening by hinges
- + Safe activation of sound via potential free contact of a master clock (or with 8...12 V~/= or 230 V~)
- + In case of triggering with 230 V applicable 230 V push-buttons have to be used only
- + Maximum safety through optocoupler input (also at 230V~)
- + Optimal pre-mounting (screw pitch correspond diameter of flush-mounting holder box)
- + Parallel connection to further gongs possible
- + VDE tested

Technical data:

i Common data.	
Multi-Volt-Use:	812 V AC/DC (250 mA) or 230 V AC (15 mA)
Sound level:	max. 86 dB(A)
Protection class:	IP 40
Temperature range:	+5 ℃ to +40 ℃
Dimensions (WxHxD):	150 x 115 x 45 mm

Mounting

ABS plastic case for wall mounting Case colour white with silver painted part



MATTIG





NEUMANN

MATTIG-SCHAUER GmbH Gorskistraße 19 :: A-1230 Wien

Tel.: +43 (1) 61055-0 :: Fax: +43 (1) 61055-30 :: e-mail: office@mattig-schauer.at :: www.mattig-schauer.at

UID-Nr.: ATU 45163905 :: ARA-Nr.: 10722