



BT-AST-LCD-INFO22Z

LCD display for entrance area of swimming pools

- + 22" full-HD LCD display (56 cm) for alternating display of time / temperature and information/messages/advertising
- + display consists of three lines:
 - + first line: time (hrs/min) or air temperature permanently or both information in rhythmic change
 - + second and third line: air- and water temperature or two water temperatures
- + temperature display in degree or 1/10 degree Celsius or Fahrenheit
- + addressing of temperature sensors adjustable
- + noiseless operation
- + for installation in entrance halls via moveable wall holder (VESA 100) which is included in delivery
- + Programming of customer specific messages (PDF, JPG or text with selectable font and character height) via PC software and USB stick for data transfer (both in delivery included)

Technical specifications:

Case:	Aluminium
Protection class:	IP30
Temperature off-set:	from -9 ... +9 °C adjustable
Power supply:	115...230 V AC, 50/60 Hz
Current consumption:	300 mA (at 230 V)
Operating temperature:	0...+40 °C
Dimensions (WxHxD):	550 x 360 x 195 mm
Weight:	8.7 kg

Options:

BT-AST15-TEMP-W2F	Water temperature sensor for 869,525 MHz radio communication (set with 2 sensors and 2 thermowells)
BT-AST15-TEMP-A/F	Air temperature sensor for radio communication (1 sensor incl. batteries)

