



G40102E

Digital LED clock with flush mounting case

- + Single-line display of hours, minutes and seconds
- + 12 or 24 hours mode
- + Modes of operation:
 - + Stand-alone quartz clock
 - + Slave clock synchronised by polarised 24 V DC minute impulses of a master clock
 - + Self-correcting slave clock synchronised by 24 V DC time code of a BMC/MPU-TC master clock
 - + Synchronisation via w482 time code signal from a series HUR master clock
 - + Synchronisation directly from DCF- or GPS-receiver
- + Green bright 7-segment LED display with 20 mm (hrs/min) & 14 mm (sec) digit height
- + Readability up to 7 m
- + Data storage up to 3 days in case of mains failure
- + Including IR handset for configuration and multifunction stopwatch operation

Technical specifications:

Case:	black, rectangular flush mounting case
Accuracy:	±0.1 sec./day (at 20...25 °C)
Power supply:	220...240 V AC / 50 Hz
Ambient temperature:	0...45 °C
Dimensions (WxHxD):	Case body 132 x 58 x 147 mm Front panel 144 x 72 x 3 mm
Weight:	approx. 1 kg

Options:

R4-DCF:	DCF-77 radio synchronisation antenna
---------	--------------------------------------



MATTIG



WENZEL



NEUMANN