



## GA45105S

### Digital LED calendar clock

- + Single-line display of day, month, hours, minutes and seconds
- + 12 or 24 hours mode
- + Modes of operation:
  - + Stand-alone quartz clock
  - + Slave clock synchronised by polarised 24 V DC minute impulses of a master clock
  - + Self-correcting slave clock synchronised by 24 V DC time code of a BMC/MPU-TC master clock
  - + Synchronisation via w482 time code signal from a series HUR master clock
  - + Synchronisation directly from DCF- or GPS-receiver
- + Green bright LED dot-matrix display with 50 mm (day, hrs, min) and 30 mm (month, seconds) digit height
- + Readability up to 20 m
- + Data storage up to 3 days in case of mains failure
- + Including IR handset for configuration

#### Technical specifications:

Case:	Aluminium, nature anodised
Accuracy:	±0.1 sec./day (at 20..25 °C)
Power supply:	220..240 V AC / 50 Hz
Ambient temperature:	0..45 °C
Dimensions (WxHxD):	550 x 90 x 58 mm
Weight:	approx. 2.5 kg

#### Options:

GA45105P:	Double sided version with ceiling bracket
R4-DCF:	DCF-77 radio synchronisation antenna
R4-TEMP:	External temperature sensor

