



**BT-ASTFR15**

**Digital time-/temperature display for baths**

- + digital time- and temperature display for indoor and outdoor use
- + display consists of three lines:
  - + first line: time (hrs/min) or air temperature permanently or both information in rhythmic change
  - + second and third line: air- and water temperature or two water temperatures
- + red LED digits with 150 mm digit height for time indication
- + red LED digits with 100 mm digit height for indication of two temperatures
- + temperature display in degree or 1/10 degree Celsius
- + visibility up to 40 m (viewing angle 120°)
- + noiseless operation
- + fixed text according to customer wishes (max. 12 characters/8 cm or max. 24 characters/ 6 cm)
- + radio remote control unit for programming in delivery included
- + radio controlled or hard-wired air temperature transmission (please see options)
- + water temperature transmission wireless only (please see options)

**Technical specifications:**

Housing:	Aluminium, black, with rounded edges
Protection class:	IP54
Temperature off-set:	from -9.9 to +9.9 °C adjustable
Power supply:	110...240 V AC
Current consumption:	<300 mA (at 230 V)
Operating temperature:	0...+50 °C
Humidity:	max. 93% at 40 °C
Dimensions (WxHxD):	1035 x 620 x 90 mm
Weight:	12 kg

**Options:**

BT-AST15-TEMP-W2F	Water temperature sensor for 869,525 MHz radio communication (set with 2 sensors and 2 thermowells)
BT-AST15-TEMP-A/F	Air temperature sensor for radio communication (1 sensor incl. batteries)
BT-AST15-TEMP/HUM-KAB5	Air temperature- and humidity sensor with 5 m cable
BT-AST15-TEMP-A/KAB5	Air temperature sensor (1 pc.) with 5 m cable



MATTIG



WENZEL



NEUMANN