



HMTT-FR25-LED Pool Clock

- + Single-line display of hours and minutes in rhythmic change with air- and water temperature
- + 12 or 24 hours mode
- + Automatic summer-/winter time changes
- + Automatic brightness adjustment
- + Modes of operation:
 - + Autonomous quartz clock
 - + Slave clock (controlled from a master clock through 24 V DC polarised minute impulses or time code)
 - + Synchronisation with DCF or GPS receiver
- + Red intensive dot matrix display with 250 mm digit height
- + Readability up to 100 m
- + Display interval between 1 to 19 s adjustable
- + Temperature calibration adjustable
- + Including radio remote control unit with 3 push-buttons for wireless adjustment of all parameters
- + Including PT100 air temperature sensor
- + Including water temperature sensor (surface type e.g. for influent pipe)

Technical data:

Housing:	Black aluminium case for wall or ceiling mounting via mounting holders
Applicability:	For mounting in moist rooms or outdoors
Accuracy:	±0.1 s / 24 h
Internal data memory:	48 h
Current consumption:	5 mA at 24 V DC impulse operation
Power supply:	230 V AC / 50 Hz ±10%
Measuring range temp.:	-30 °C ... +60 °C (measuring every minute)
Accuracy temp.:	±1 °C (calibration range ±9 °C)
Ambient temperature:	-20 °C ... +40 °C
Dimensions (WxHxD):	1200 x 330 x 92 mm
EMC:	EN61000-6-3:2001, EN61000-6-2:2005



Analogue Clocks
Master Clocks
Clock Centrals
Digital Clocks
Wireless Master Clock System
Scoreboards



Options:

HM-DCF2: DCF-77 radio synchronisation antenna
HM-GPS2: GPS reception antenna
HM-TTFR25PW-LED: Double sided version (case depth 130 mm)
Versions with 150 / 190 mm digit height



MATTIG



WENZEL



NEUMANN