



## PSG115-12/24V Universal Signaller

- + To be used for break or alarm signalling in schools, industry, public buildings, and so on
- + Double-Pressure Chamber-Loudspeaker-System
- + Solid Loudspeaker grill made of anodised aluminium
- + 2 separate channels for hoot differentiation (e.g. alarm signal), whereas each channels can be adjusted individually for sound level, signal tonality, signal length and time for sound level increase
- + Adjustable signal types:
  - + As long as control through a master clock
  - + 30 seconds fixed
  - + Melody sequels
- + 2 different signal bell-/hooting signal selectable
- + 5 different melodies (e.g. 2 sounds, 3 sounds, Westminster) selectable
- + 8 different siren-/alarm signals selectable
- + „Beep“ signal selectable
- + Manual deactivation of signal sound with integrated pushbutton possible (acknowledge function)
- + Time for sound level increase (e.g. at time of alarm) up to 30 s continuous adjustable
- + Green Checking LED (unit in operation)
- + Parallel connection of several units possible

### Technical Specifications:

Colour:	Anthracite grey (RAL7016)
Adjustable Sound level:	80 ... 115 dB(A) for each channel and each sound
Permanent operation:	105 dB/A or 115 dB/A max. 10 min.
On-time:	100%
Protection class:	IP54
Temperature range:	-20 °C ... +50 °C
Power supply:	12 ... 24 V AC/DC
Nominal current:	1 A
Dimensions:	158 x 243 x 80 mm
Weight:	max. 1.3 kg

### Mounting

ASA plastic case for table-, wall- or ceiling mounting capable

