



MPU-TC404P

Microprocessor controlled master clock

- + Four independent slave clock lines
- + Connection of up to 4x 80 impulse controlled or up to 4x 80 self-correcting Time Code slave clocks (max. output current 1 A each line; totally max. 350 clocks)
- + Polarised 24 V DC outputs for minutes-, ½ minutes - or seconds impulses respectively time code for operation of self-correcting and self-setting slave clocks
- + Mixed operation of slave clocks and self-correcting clocks possible
- + Impulse length adjustable
- + Impulse to break rate programmable
- + Automatic adjustment of slave clocks after mains failure
- + Electronic impulse memory for min. 5 years
- + Automatic summer-/winter daylight-saving time programmable
- + Everlasting calendar
- + Automatic free programmable holiday calendar with or without holidays depending on Easter
- + Electronic short-circuit protection
- + Electronic low voltage cut-off (18 V)
- + Two-lined liquid crystal display (LCD) with 8.5 mm digit height (20 characters per line)
- + Indication of weekday, hours, minutes, seconds, date, summer-/winter time and DCF reception
- + Synchronisation through:
 - + DCF-77 (for time and summer-/winter time changes)
 - + GPS system (for time and summer-/winter time changes)
 - + 24 V DC polarised minute impulses (master/slave operation)
- + Text message on display in case of missing DCF/GPS synchronisation after 48 hours
- + Error text message in case of short-circuit on a slave line
- + Accuracy ± 0.1 s/day at 25 °C (without DCF synchronisation)
- + RS232 and RS485/422 Interface:
 - + One serial RS232 and RS485 output
 - + Interval for output of Schauer time telegram programmable for output every second, every minute, all 5 minutes or on demand
 - + User selection of 1200, 2400, 4800, 9600 or 19200 baud, 7 or 8 data bits and uneven, even or no parity



MATTIG



WENZEL



NEUMANN

Signalling device

- + Four potential free switchover contacts
- + Dialogue programming with menu navigation
- + 99 day programs with max. 99 program steps each
- + Period table with 99 program lines
- + Copy function for day programs
- + Switching times per second
- + On/Off- and timer-functions with 1 s ... 59 min. run time
- + 32 different timer lengths programmable
- + Checking of programming via display
- + Single-, partial- and complete deletion of programs
- + Program memory for 99 day programs with totally 9801 (=99x99) program steps
- + Alarm relay function: The relay switches off in case of an alarm condition (short-circuit on slave line or missing DCF/GPS synchronisation after 48 hours).
- + Relay function depending on summer-/winter time status: The relay is only active either at current summer time or winter time.
- + Contact rating 250 V / 4 A (ohmic load)

Mounting

Two plastic cases for surface wall mounting and mounting on top hat rail according to DIN 46277 sheet 3

Colour: Upper part light grey, lower part dark grey

Dimensions (WxHxD): 241 x 313 x 87 mm per housing

Power supply: 220...240 V / 47...63 Hz

Power consumption: 110 VA

Ambient temperature: 0...40 °C

Options:

DCF-ANT02: DCF-77 radio synchronisation antenna

GPS-ANT8: GPS reception antenna with DCF output

MPU-AK1.8: 24 V DC / 1.8 Ah power reserve



MATTIG



WENZEL



NEUMANN